




BLACK BOX®

© Copyright 1995. All rights reserved.
Black Box Corporation.

The Source for Connectivity®

Mini Driver MP Dual Line Driver Card



Two complete RS-232 line drivers in one convenient, space-saving card!

Key Features

- ▶ Includes two complete RS-232 line drivers
- ▶ Full V.54/V.52 diagnostics
- ▶ Supports multipoint—up to 50 drops
- ▶ Fits in MicroRACK System

Overview

The Mini Driver MP Dual Line Driver Card is a dual rack card incorporating two short range modems. Both units support asynchronous data rates to 115.2 Kbps over 1 or 2 twisted pairs and support distances to 9.4 miles. The Card features six easy-to-read front panel LEDs and incorporates Silicon Avalanche Diodes for protection against the damaging effects of nearby

lightning strikes and other harmful transients.

Up to 50 terminal drops can be handled in a multipoint polling environment. For RS-485 and serial printer applications requiring hardware handshaking, the Card passes one control signal in each direction. The Card may be configured for high or low impedance operation and the carrier may be set to

“constantly on” or “controlled by RTS”.

The latest surface mount technology is used to attain high quality short range modem performance in a convenient rack card. The card is available with RJ-11 or RJ-45 rear interface cards. For workgroup and desktop communications, the Card can be mounted in the MicroRACK system.

Specifications

Protocol—Asynchronous

Operation—2-wire half-duplex, 4-wire full/half-duplex

Connectors—(4) RJ48

Size—Rear Card: 2.75" x 3.25" (7 x 8.3 cm); Front Card: 4.25" x 3" (11.4 x 7.6 cm)

Weight—1 lb. (0.5 kg)

Ordering Information

This information will help you place your order quickly.

PRODUCT NAME

ORDER CODE

Mini Driver MP Dual Line Driver CardME778C-RJ11/RJ45